AGRILUX

A professional single-sided aluminium stepladder with 10cm-deep steps welded to the stiles and spaced 27cm apart. Its tapered design makes it easy to position between tree branches, while the rear support bar provides stability. Designed especially for agricultural work such as fruit picking and pruning.

TECHNICAL SPECIFICATIONS

- Number of steps: 4 to 14;
- Step spacing: 27cm;
- Step depth: 10cm;
- Non-slip feet with ergonomic design;
- Rear support bar with spike;
- Anti-opening strap;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.

OPTIONS

- Spikes (front profiles)
- Telescopic prop







Agrilux 6 steps

Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 2 years WARRANTY | professional use | 150 KG

No. of steps	4	5	6	7	8	9	10	12	14
Overall height *(m)*	1.58	1.85	2.12	2.39	2.66	2.93	3.20	3.74	4.28
Overall closed height *(m)*	1.71	1.98	2.25	2.52	2.79	3.06	3.33	3.87	4.41
Width *(m)*	0.61	0.68	0.75	0.82	0.89	0.96	1.03	1.17	1.31
Weight *(kg)*	5.00	7.00	9.00	11.00	13.00	15.00	17.00	21.00	25.00
Reference	10213.5	10213.2	10213.1	10213.3	10213	10213.4	10214	10215	10216