FIBREGLASS

ALFA FIBRA VIDRO

Professional stepladder made of fibreglass, with aluminium steps 8cm deep and spaced 25cm apart. Provides electrical insulation, tested at 5000 volts. Features a tray, tool holder and spacious platform (25.50x28cm). Very comfortable and safe. Ideal for workers operating near sockets, cables or electrical power sources.



Alfa Fibra Vidro 7 steps

TECHNICAL SPECIFICATIONS

- Number of steps: 5 to 8;
- Step spacing: 25cm;
- Depth: 8cm;
- Platform: 25.50x28cm;
- Reinforced polypropylene platform;
- Anti-opening safety hook;
- Non-slip rubber feet;
- Guardrail height: 60cm;
- User and maintenance manual;
- Certificate of conformity with EN131;
- Identification label.

TESTED TO MEET THE FOLLOWING PROPERTIES:

Dielectric strength	7-10 kV/mm	DIN 53481
Insulation resistance	10-10 Ω	DIN 53482
Dielectric constant at 50Hz	4-6	DIN 53483
Dissipation factor at 50 Hz	0.03-0.04 tgδ	DIN 53483



Tool tray (detail)



Decree-Law 50/2005 Portugal | Certified EN 131 Standard | Certified EN 50528 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	5	6	7	8
Platform height *(m)*	1.16	1.39	1.61	1.85
Working height *(m)*	3.16	3.39	3.61	3.85
Overall closed height *(m)*	1.95	2.20	2.45	2.70
Width *(m)*	0.49	0.51	0.54	0.56
Closed width *(m)*	0.16	0.16	0.16	0.16
Weight *(kg)*	8.40	9.40	10.60	11.80
Reference	**10256**	**10257**	**10258**	**10259**