ARTICULADA

Aluminium articulated ladder, convertible into 2 positions: stepladder and leaning ladder. With 30x30mm rungs spaced 28cm apart. 36cm wide, very practical, easy to handle and very sturdy. Features an aluminium stabiliser bar. Ideal for simple jobs in confined spaces.



Articulada 2 x 7 rungs

TECHNICAL SPECIFICATIONS

- Number of rungs: 2x4 to 2x8;
- Step spacing: 28cm;
- Rungs: 30x30mm;
- Width: 36cm;
- Profile: 65x25mm;
- Steel hinges with anti-corrosion treatment;
- Stabiliser base (stabiliser bar);
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.







Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 3 years WARRANTY | professional use | 150 KG

No. of steps	2 x 4	2 x 5	2 x 6	2 x 7	2 x 8
Height in stepladder position *(m)*	1.27	1.54	1.81	2.08	2.35
Closed ladder height *(m)*	1.37	1.64	1.91	2.18	2.45
Extended ladder height *(m)*	2.53	3.09	3.65	4.21	4.78
Closed width *(m)*	0.21	0.21	0.21	0.21	0.21
Weight *(kg)*	7.00	8.00	9.00	10.00	11.00
Reference	**10234**	**10235**	**10236**	**10237**	**10238**

When calculating the working height, allow 2m for the user with arms outstretched.