AUSTIN

Professional telescopic platform made of aluminium. With 20cm-deep steps spaced 30cm apart. Fitted with telescopic legs adjustable every 5cm, allowing the operator to work as close as possible to the work area. Ideal for work on staircases, pavements, near production lines and around obstacles.

PROTECTION & SAFETY 360°

TECHNICAL SPECIFICATIONS

- Number of steps: 2 to 4;
- Step spacing: 30cm;
- Step depth: 20cm;
- Toeboard height: 10cm;
- Guardrail height: 1.10m;
- Telescopic adjustment: every 5mm;
- Platform: 75x75cm;
- Non-slip rubber feet;
- Telescopic legs adjustable to the terrain;
- User and maintenance manual;
- Identification label.



ADJUSTABLE FEET

Austin 2 steps

Foot adjustable every 5cm up to a maximum height of 30cm





Decree-Law 50/2005 Portugal · Certified EN 14122 Standard · 5 years WARRANTY · professional use · 150 KG

No. of steps	2	3	4
Platform height *(m)*	0.61 - 0.91	0.91 - 1.21	1.21 - 1.51
Overall height *(m)*	1.71 - 2.01	2.01 - 2.31	2.61 - 2.91
Working height *(m)*	2.60 - 2.90	2.90 - 3.20	3.20 - 3.50
Dimensions *(m)*	0.86 x 1.09	0.86 x 1.29	0.86 x 1.49
Weight *(kg)*	28.00	32.00	36.00
Reference	10889	10890	10891