BRABUS

Professional individual work platform with a folding guardrail system giving the worker 360º protection. It has 8cm-deep steps spaced 24cm apart, and its Ø40mm tubular structure provides greater stability and comfortable climbing. Access width is 53cm. Ideal for a wide range of professional tasks.

PROTECTION & SAFETY 360°

TECHNICAL SPECIFICATIONS

- Number of steps: 3 to 6;
- Step spacing: 24cm;
- Step depth: 8cm;
- Platform: 47x55cm;
- Toeboard height: 10cm;
- Transport wheels: Ø125 mm;
- Reinforced marine plywood platform;
- Large tool holder;
- System preventing accidental closing;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.

TOP GAMA EST. TOP GAMA 1978 JORMAX INDÚSTRIA LDA.



Brabus 4 steps





Decree-Law 50/2005 Portugal · Certified EN 131-7 Standard · 5 years WARRANTY · professional use · 150 KG

No. of steps	3	4	5	6
Platform height *(m)*	0.72	0.96	1.20	1.44
Overall height *(m)*	1.75	1.99	2.23	2.47
Working height *(m)*	2.72	2.96	3.20	3.44
Width *(m)*	0.77	0.77	0.77	0.77
Closed width *(m)*	0.12	0.12	0.12	0.12
Weight *(kg)*	13.00	16.00	18.00	19.00
Reference	**23063**	**23064**	**23065**	**23066**