DESLIZ

Sliding ladder for professional use, made of extruded aluminium and fitted with a sophisticated connection and sliding system on a rail. With an external width of 38.50cm and 8cm-deep rungs spaced 25cm apart, the ladder can be left open or in the rest position. Ideal for shelving, libraries and archives.



Desliz 8 rungs

TECHNICAL SPECIFICATIONS

- Number of steps: 8 to 18;
- Step spacing: 25cm;
- Step depth: 8cm;
- Profile: 80x25mm;
- Wheels: Ø8cm;
- Automatic self-locking system;
- Rail system (components in the table below);
- User and maintenance manual;
- Certificate of conformity with EN131;
- Identification label.

OPTIONS

- Hooks for portable ladder (Ø50/36mm)
- Aluminium tube 3.00m
- Intermediate bracket (1 unit per 1.00m)
- Bracket with right-hand stop
- Bracket with left-hand stop

Aluminium tube + brackets



Telescopic brackets



Hooks (optional)



Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	8	10	12	14	16	18
Overall height *(m)*	2.32	2.78	3.26	3.70	4.17	4.63
Working height *(m)*	3.82	4.28	4.76	5.20	5.67	6.13
Ladder-to-wall distance *(m)*	0.98	1.16	1.35	1.54	1.73	1.91
Weight *(kg)*	7.20	8.50	9.30	10.80	12.00	13.10
Reference	10846	10847	10848	10849	10849.1	10849.2