DOUBLE

Two-section ladder with 2 convertible parts (A position), made of aluminium, with rungs spaced 28cm apart. The ladder has a top base, a tool holder for the user and a bar that prevents accidental opening, for greater safety. Ideal for professional work at greater heights, with no need to lean it against a support.



Double 2 x 12 rungs

TECHNICAL SPECIFICATIONS

- Number of steps: 2x8 to 2x17;
- Step spacing: 28cm;
- Width: 48cm (front) + 42cm (rear);
- Non-slip feet with ergonomic design;
- Internal nylon reinforcement at the stabiliser insertion point;
- Steel fittings with anti-corrosion treatment;
- Anti-slide safety device;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.



Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	2 x 8	2 x 12	2 x 14	2 x 17
Overall closed height *(m)*	1.88	2.98	4.10	4.88
Working height *(m)*	3.88	3.98	5.10	5.88
Front section width *(m)*	0.42	0.42	0.42	0.42
Widest section width *(m)*	0.48	0.48	0.48	0.48
Weight *(kg)*	19.00	27.00	38.00	46.00
Reference	**20178**	**20179**	**20180**	**20181**