ES600

A professional access ladder made of sturdy aluminium, with 8cm steps spaced 28cm apart. Fitted with handrails and guardrails. It is a very strong structure. The PVC feet give the ladder great stability. Ideal for professional access to upper floors or any elevated point (roofs, etc.).




ES600 8 steps


TECHNICAL SPECIFICATIONS

- Number of steps: 5 to 16;
- Step spacing: 28cm;
- Step depth: 8cm;
- Profile: 65x25mm;
- Non-slip feet;
- Reinforced stiles;
- Reinforcing crossbars on the widest steps;
- Access handrails (on both sides);
- User and maintenance manual;
- Certificate of conformity with EN131;
- Identification label.

See the available components at www.jormax.com.







Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	5	6	7	8	9	10	11	12	13	14	15	16
Top step height *(m)*	1.27	1.53	1.79	2.05	2.31	2.57	2.83	3.09	3.35	3.61	3.87	4.13
Overall height *(m)*	2.39	2.67	2.95	3.23	3.51	3.79	4.07	4.35	4.63	4.91	5.19	5.47
Distance to wall *(m)*	0.62	0.73	0.83	0.94	1.04	1.15	1.25	1.36	1.46	1.57	1.68	1.78
Weight *(kg)*	11.00	12.00	13.00	14.00	15.00	16.00	17.00	18.00	19.00	20.00	21.00	22.00
Reference	**10110**	**10111**	**10112**	**10113**	**10114**	**10115**	**10116**	**10117**	**10118**	**10119**	**10120**	**10121**

When calculating the working height, allow 2m for the user with arms outstretched.