J500 - PLATAFORMA FIXA

Adjustable two-section ladder with fixed platform for below-ground levels. It has a safe front exit, supported by a platform with articulated support feet. The steps are 8cm deep and spaced 28cm apart. The handrails ensure stability when climbing. The telescopic system provides versatility for multiple access points. Ideal for work such as excavations and foundations.



J500 8 - 11 steps

TECHNICAL SPECIFICATIONS

- Number of steps: from 5-8 to 11-16;
- Step spacing: 28cm;
- Step depth: 8cm;
- Profile: 65x25mm;
- Platform: 70x54cm;
- Wheels: Ø150mm;
- Width: 67cm;
- Safety gate;
- Aluminium platform;
- Access handrails;
- User and maintenance manual;
- Identification label.







Decree-Law 50/2005 Portugal · 5 years WARRANTY · professional use · 150 KG

No. of steps	5 - 8	8 - 11	11 - 16
Minimum overall height *(m)*	1.21	1.96	2.71
Maximum overall height *(m)*	1.96	2.72	3.97
Closed dimensions *(m)*	2.59 x 0.67 x 0.90	2.86 x 0.67 x 0.90	3.67 x 0.67 x 0.90
Weight *(kg)*	29.00	33.00	39.00
Reference	15440	15441	15442

When calculating the working height, allow 2m for the user with arms outstretched.