# J600 - PLATAFORMA AJUSTÁVEL

Telescopic aluminium ladder with platform, for access to another level. Height-adjustable in 28cm increments, it gives access to lorry bodies, trenches, excavations, tanks and lift pits. Includes 2 hooks for crane lifting and 2 telescopic legs with swivel feet for greater stability on uneven ground. Ideal for professional use.




## TECHNICAL SPECIFICATIONS

- Height adjustable in 28cm increments;
- Telescopic access flight;
- Platform: 45x50cm;
- Non-slip rungs: 28x28mm;
- Base width: 76cm;
- Removable Ø 32mm guardrails;
- 2 rear telescopic legs of 28cm with swivel feet;
- 2 hooks for crane lifting and transport;
- Transport wheels (ref. 15446);
- Non-slip PVC feet;
- Maximum load: 150kg.













Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

| | | | |
|---|---|---|---|
| **No. of steps** | 4+3 | 6+4 | 12+4 |
| **Closed height** *(m)* | 2.15 | 2.73 | 3.01 |
| **Min. platform height** *(m)* | 1.00 | 1.52 | 3.08 |
| **Max. platform height** *(m)* | 1.52 | 2.32 | 3.86 |
| **Closed dimensions** *(m)* | 2.15 x 0.58 x 0.23 | 2.73 x 0.58 x 0.23 | 3.02 x 0.77 x 0.23 |
| **Weight** *(kg)* | 18.00 | 19.00 | 21.50 |
| **Reference** | **15444** | **15445** | **15446** |