SCAFFOLDING

JS TOWER

Ultra-compact professional aluminium scaffolding, designed for safe and quick assembly by one person, without having to return to the ground during assembly. The JS Tower scaffold offers the flexibility to work at different heights, making it the ideal choice for indoor installations, painting and maintenance work, with a working height of up to 6.00 metres.



JS TOWER

TECHNICAL SPECIFICATIONS

- Rung spacing: 30 cm;
- 4 wheels: Ø 125 mm (2.25 kg/wheel);
- 4 adjustable spindles: 150 mm (0.85 kg/spindle);
- 1.00 m double guardrail;
- Platform with trapdoor: aluminium frame, wooden surface;
- Overall height: 5.17 m (111 kg);
- Maximum height above ground: 4.17 m;
- Maximum working height: 6.17 m;
- Frame dimensions: 1.10 x 0.74 m;
- Base dimensions: 1.00 x 0.60 m (8.56 kg);

ADVANTAGES

- Can be assembled by one person;
- Quick and safe assembly (5 metres in under 10 minutes);
- Rigid, lightweight, sturdy and durable;
- The base forms a trolley that holds all the components;
- Requires minimal space in use, even in small areas;
- Fits in commercial vehicles and lifts;



Decree-Law 50/2005 Portugal | Certified EN 1004 Standard | 5 years WARRANTY | professional use

Platform height *(m)*	0.87	1.17	1.77	2.07	2.97	3.27	3.87	4.17
Overall height *(m)*	1.87	2.17	2.77	3.07	3.97	4.27	4.87	5.17
Working height *(m)*	2.87	3.17	3.77	4.07	4.97	5.27	5.87	6.17
Number of platforms	1	1	1	1	2	2	2	2
Number of toeboard kits	1	1	1	1	1	1	1	1
Number of 4-rung modules	2	4	2	4	4	6	4	6
Number of 3-rung modules	3	0	4	2	4	2	6	4
Number of guardrails	3	3	4	4	6	6	7	7
Weight *(kg)*	47.5	49	79	80.5	100.5	102	109	111
Reference	700001	700002	700003	700004	700005	700006	700007	700008