MAXILADDER DUPLA

Professional 2-section convertible ladder: stepladder and leaning ladder positions, made of ribbed extruded aluminium. With 28cm between rungs, it features an advanced automatic swaging system. The front section is 43cm wide and the wide section 48cm. Ideal for all types of professional work.

Mechanical version (with rope) available - SEE www.jormax.com

TECHNICAL SPECIFICATIONS

- Number of steps: 2x6 to 2x14;
- Step spacing: 28cm;
- Stabiliser base (from 3.00m in height);
- Non-slip rubber feet;
- Safety strap preventing accidental opening;
- Anti-opening bars;
- Anti-slide safety device;
- Certificate of conformity with EN131;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.



Maxiladder Dupla 2 x 6 rungs

Ladder fully closed







Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	2 x 6	2 x 7	2 x 8	2 x 9	2 x 10	2 x 11	2 x 12	2 x 13	2 x 14
Height in stepladder position *(m)*	1.64	1.91	2.18	2.44	2.70	2.96	3.23	3.48	3.74
Overall extended height *(m)*	2.90	3.46	4.02	4.30	4.86	5.42	5.70	6.84	6.79
Closed ladder height *(m)*	1.80	2.08	2.36	2.64	2.92	3.20	3.48	3.76	4.04
Profile *(mm)*	65 x 25	65 x 25	65 x 25	65 x 25	65 x 25	65 x 25	65 x 25	73 x 25	73 x 25
Weight *(kg)*	9.00	10.00	11.00	12.00	13.00	15.00	16.00	18.00	19.00
Reference	10176	10177	10178	10179	10180	10181	10182	10183	10184

When calculating the working height, allow 2m for the user with arms outstretched.