# MAXILADDER SUPER TRIPLA

Professional 3-section convertible ladder: stepladder and leaning ladder positions, made of ribbed extruded aluminium. With 2.7cm rungs spaced 28cm apart, it features an advanced automatic swaging system. The top section is 36.50cm wide, the middle section 42.30cm and the base 48cm. Ideal for all types of professional work.



Illustrative image of the Maxiladder Super Triple 3x8 (the other models follow this example)

## TECHNICAL SPECIFICATIONS

- Number of rungs: 3x12 to 3x16;
- Step spacing: 28cm;
- Rungs: 27x27mm;
- Width: 48+42.30+36.50cm;
- Stabiliser base;
- Non-slip rubber feet;
- Safety strap preventing accidental opening;
- Steel fittings with anti-corrosion treatment;
- User and maintenance manual;
- Identification label.

**See the available components at www.jormax.com.**

WHAT DISTINGUISHES THE **MAXILADDER SUPER TRIPLA** FROM THE **MAXILADDER TRIPLA?**

Includes **sliding wheels** and **greater height**:

| | TRIPLE | SUPER TRIPLE |
|---|---|---|
| **Height in stepladder position** *(m)* | 5.89 | 4.50 |
| **Overall closed height** *(m)* | 3.91 | 4.60 |
| **Overall extended height** *(m)* | 8.53 | **11.90** |


These are the maximum sizes available for these ladders.

### Sliding wheels



### Aluminium hinges





Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

| | | | |
|---|---|---|---|
| **No. of steps** | 3 x 12 | 3 x 14 | 3 x 16 |
| **Height in stepladder position** *(m)* | 3.40 | 4.00 | 4.50 |
| **Overall closed height** *(m)* | 3.50 | 4.10 | 4.60 |
| **Overall extended height** *(m)* | 8.55 | 10.20 | 11.90 |
| **Profile** *(mm)* | 84 x 27 | 100 x 27 | 115 x 27 |
| **Weight** *(kg)* | 26.50 | 32.50 | 40.00 |
| **Reference** | **10873** | **10875** | **10876** |

When calculating the working height, allow 2m for the user with arms outstretched.