MG-EXTEND

Professional extension ladder consisting of 2 sections. With 30x30mm rungs spaced 28cm apart, a width of 35cm on section 1 and 43cm on section 2. The ladder is supported by 2 die-cast aluminium hooks for greater safety. Ideal for occasional access to roofs, caged access ladders, residential buildings and similar.



MG-Extend 2x6 rungs

TECHNICAL SPECIFICATIONS

- Number of rungs: 2x6 to 2x13;
- Step spacing: 28cm;
- Rungs: 30x30mm;
- Ladder width: 35 + 43cm;
- Profile: 85x25/ 73x25mm;
- Die-cast aluminium hooks;
- Non-slip rubber feet;
- Certificate of conformity with EN131;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.

OPTIONS

- Support bar (to support the ladder by its hooks)
- Wall latch (to store the ladder upright permanently)

Support bar



Wall latch



Support hooks





Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	2 x 6	2 x 7	2 x 8	2 x 9	2 x 10	2 x 11	2 x 12	2 x 13
Overall closed height *(m)*	1.80	2.08	2.36	2.64	2.92	3.20	3.48	3.76
Overall extended height *(m)*	2.62	3.18	3.74	4.30	4.86	5.42	5.98	6.54
Profile *(mm)*	65 x 25	65 x 25	65 x 25	65 x 25	65 x 25	65 x 25	65 x 25	73 x 25
Weight *(kg)*	9.00	10.00	11.00	12.00	13.00	14.00	15.00	16.00
Reference	10715	10716	10717	10718	10719	10720	10721	10722

When calculating the working height, allow 2m for the user with arms outstretched.