MULTIFLEX PLUS

Multi-function telescopic ladder made of ribbed extruded aluminium, for use in stepladder or leaning ladder position. With rungs 27mm deep and spaced 28cm apart, and a closed ladder width of 15cm. Easy to transport and store. Ideal for professional work at different levels.

TECHNICAL SPECIFICATIONS

- Number of rungs: 8+8 to 12+12;
- Step spacing: 28cm;
- Rungs: 27x27mm;
- Internal width: 36.50cm;
- Internal profile: 52x27mm;
- External profile: 64x30mm;
- Steel hinges with anti-corrosion treatment;
- Stabiliser bar;
- Nylon-coated steel locking hooks;
- Ergonomic non-slip rubber feet;
- Tool tray;
- User and maintenance manual;
- Identification label.


See the available components at www.jormax.com.

The **8+8-rung** model complies with standard **EN131-4**.



Ladder fully closed







Multiflex Plus 8 + 8 rungs

Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	8 + 8	10 + 10	12 + 12
Closed ladder height *(m)*	1.25	1.53	1.81
Height in stepladder position *(m)*	1.96	2.51	3.10
Height in ladder position *(m)*	4.10	5.22	6.35
Width *(m)*	0.63	0.63	0.75
Weight *(kg)*	11.00	13.20	15.00
Reference	**30770**	**30771**	**30772**

When calculating the working height, allow 2m for the user with arms outstretched.