MULTILADY

Professional telescopic ladder for use in leaning ladder, stepladder and platform positions. Can also be used on uneven ground. 30x30mm rungs spaced 28cm apart, overall width of 78cm and closed width of 27cm. Adjustable to various heights. Easy to transport and store (compact). Ideal for professional, DIY and domestic use.

TECHNICAL SPECIFICATIONS

- Number of rungs: 12;
- Step spacing: 28cm;
- Rungs: 30x30mm;
- Width: 78cm (with stabiliser bar);
- Closed width: 27cm;
- Dimensions in platform position: 89x28cm;
- Profile: 64x24mm (internal)/ 72x27mm (external);
- Transport dimensions: 35x45x97cm;
- Non-slip PVC feet;
- Automatic steel joints;
- Double ground stabiliser;
- User and maintenance manual;
- Certificate of conformity with EN131;
- Identification label.

See the available components at www.jormax.com.




Multilady 12 rungs

Leaning ladder position



Use on uneven ground





Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 3 years WARRANTY | professional use | 150 KG

No. of steps	12
Platform height *(m)*	0.94
Overall closed height *(m)*	0.96
Height in stepladder position *(m)*	1.76
Height in ladder position *(m)*	3.63
Weight *(kg)*	15.00
Reference	**10233**

When calculating the working height, allow 2m for the user with arms outstretched.