MULTIUSO

Professional multipurpose ladder made of extruded aluminium, for use in stepladder, leaning ladder or work platform position (platform sold separately). With rungs spaced 28cm apart and a closed width of 28cm, it is a sturdy 4-section construction with robust rectangular crossbars. Ideal for a wide range of professional work.



Multiuso 4 x 3 rungs

TECHNICAL SPECIFICATIONS

- Number of rungs: 4x3 and 4x4;
- Step spacing: 28cm;
- Closed width: 28cm;
- Stile profile: 65x25mm;
- Automatic quick-positioning hinges;
- Ergonomic non-slip rubber feet;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.

OPTIONS


- Platform (for 4x3 ladder)

Ladder fully closed



Optional - platform





Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 3 years WARRANTY | professional use | 150 KG

No. of steps	4 x 3	4 x 4
Height in platform position *(m)*	0.96	1.24
Height in stepladder position *(m)*	1.72	2.84
Height in ladder position *(m)*	3.54	4.66
Weight *(kg)*	14.00	16.00
Reference	**10226**	**10227***

*Model 10227 does not comply with EN131.

When calculating the working height, allow 2m for the user with arms outstretched.