PALCO 1 SUBIDA

A professional warehouse platform made of ribbed extruded aluminium, with 20cm-deep steps spaced 23cm apart. It features an automatic brake system that engages when the platform is in the working position and releases when the operator steps down. Ideal for accessing and servicing vehicles, raised floors and machinery.

TECHNICAL SPECIFICATIONS

- Number of steps: 3 to 8;
- Step spacing: 23cm;
- Step depth: 20cm;
- Platform: 60x80cm;
- Guardrail + toeboard height: 1.00m;
- Stile profile: 65x25mm;
- Access width: 66cm;
- Access angle: 55º;
- Wheels: Ø125mm;
- Near-vertical rear and sides;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.

OPTIONS

- 2nd side handrail + side protection
- Front protection
- Platform without wheels
- Self-closing gate







Palco 1 Subida 5 steps

Decree-Law 50/2005 Portugal | Certified EN 131-7 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	3	4	5	6	7	8
Platform height *(m)*	0.73	0.96	1.19	1.42	1.65	1.88
Overall height *(m)*	1.64	1.87	2.10	2.33	2.56	2.79
Working height *(m)*	2.73	2.96	3.19	3.42	3.65	3.88
Width x length *(m)*	0.77 x 1.24	0.82 x 1.41	0.88 x 1.58	0.94 x 1.75	1.00 x 1.92	1.06 x 2.09
Weight *(kg)*	38.00	41.00	45.00	48.00	52.00	56.00
Reference	**10311**	**10312**	**10313**	**10314**	**10315**	**10316**