PRIME DUPLA

A professional two-section ladder, swaged using an innovative rung system that keeps the rung level at all times during use. The rungs are 30mm deep and spaced 30cm apart. The ladder is fitted with ergonomic non-slip feet, durably swaged. Ideal for the most demanding professional work.

TECHNICAL SPECIFICATIONS

- Number of rungs: 6+7 to 13+14;
- Step spacing: 30cm;
- Rungs: 30x30mm;
- Width: 48.5 + 42.30cm;
- Patented adjustable base;
- Sliding wheels;
- Adjustable base stabiliser;
- Extension locking device (prevents the ladder from moving when the limit is reached);
- Die-cast aluminium opening system;
- Adjustment up to 16cm, in 2cm increments;
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.



Prime Dupla 8 + 9 rungs

Flat rungs (detail)



Use on uneven ground





Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	6 + 7	8 + 9	10 + 11	13 + 14
Stepladder height *(m)*	2.10	2.70	3.30	4.10
Overall closed height *(m)*	2.25	2.85	3.45	4.35
Overall extended height *(m)*	3.45	4.65	5.85	7.65
Width (without stabiliser bar) *(cm)*	42.30 + 48.50	42.30 + 48.50	42.30 + 48.50	42.30 + 48.50
Weight *(kg)*	12.00	14.00	16.50	23.00
Reference	**10755**	**10756**	**10757**	**10759**

When calculating the working height, allow 2m for the user with arms outstretched.