PRIME SIMPLES

A professional single ladder, swaged using an innovative rung system that keeps the rung level at all times during use. The rungs are 30mm deep and spaced 30cm apart. The ladder is fitted with ergonomic non-slip feet, durably swaged. Ideal for the most demanding professional work.



Prime Simples 13 rungs

TECHNICAL SPECIFICATIONS

- Number of rungs: 7 to 15;
- Step spacing: 30cm;
- Rungs: 30x30mm;
- Profile: 67x27mm;
- Width (without stabilisers): 42.30cm;
- Overall height: 2.30 to 4.70m;
- Non-slip feet and foot pads;
- Stabiliser bar (from 3.00m in height);
- User and maintenance manual;
- Identification label.

See the available components at www.jormax.com.







Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	7	9	11	13	15
Overall height *(m)*	2.30	2.90	3.50	4.10	4.70
Width (without stabiliser bar) *(m)*	0.42	0.42	0.42	0.42	0.42
Profile *(mm)*	67 x 27	67 x 27	67 x 27	67 x 27	67 x 27
Weight *(kg)*	4.30	5.40	8.50	9.50	10.50
Reference	**10749**	**10750**	**10751***	**10752***	**10752.1***

***Stabiliser bar included. Under EN131, a stabiliser bar is mandatory from 3.00m in height.**

When calculating the working height, allow 2m for the user with arms outstretched.