RAMPAS RLP DOBRÁVEL

Folding aluminium loading ramp for vehicles. It folds on its central hinge (for easier transport and storage). Available in various lengths and load capacities. Perforated surface. Very lightweight and easy to handle. Ideal for motorcycles, quad bikes, small tractors, construction equipment and cleaning machines.

TECHNICAL SPECIFICATIONS

- Width: 20cm;
- Length: 1.50 to 2.50m;
- Weight: 5.00 to 7.50KG;



RL RAMPS

Aluminium loading ramp for vehicles. Available in various lengths and load capacities. Perforated surface. Very lightweight and easy to handle. Ideal for motorcycles, quad bikes, small tractors, construction equipment and cleaning machines.

TECHNICAL SPECIFICATIONS

- Width: 20cm;
- Length: 1.50 to 3.00m;
- Weight: 4.00 to 8.00KG;



Decree-Law 50/2005 Portugal

5 years WARRANTY

RAMP **RLP FOLDING**			
Model	RLP - 15	RLP - 20	RLP - 25
Length *(m)*	1.50	2.00	2.50
Width *(m)*	0.20	0.20	0.20
Concentrated load capacity *(kg)*	389.00	289.00	229.00
Load capacity with 0.50m wheelbase *(kg)*	570.00	384.00	292.00
Load capacity with 0.75m wheelbase *(kg)*	700.00	440.00	328.00
Load capacity with 1.00m wheelbase *(kg)*	780.00	520.00	364.00
Profile height *(cm)*	3.50	3.50	3.50
Weight *(kg)*	5.00	6.50	7.50
Reference	**10673**	**10674**	**10675**

RAMP **RL**			
RL - 15	RL - 20	RL - 25	RL - 30
1.50	2.00	2.50	3.00
0.20	0.20	0.20	0.20
522.00	357.00	250.00	175.00
756.00	472.00	316.00	216.00
936.00	548.00	356.00	240.00
1 048.00	648.00	400.00	264.00
3.50	3.50	3.50	3.50
4.00	5.00	6.00	8.00
10676	**10677**	**10678**	**10679**

Concentrated load capacity means a load placed at a single point.