RAMPAS DE CARGA

Loading ramps made of extruded aluminium with very high mechanical strength. Can withstand loads of up to 9320kg. Fitted with vehicle attachment brackets. Not recommended for vehicles with steel tracks. The minimum distance between machine wheels is 1.40m, except for AL, BL, CL, DL (1.00m). Ideal for loading aerial platforms and other machinery.





Rampas de carga

Decree-Law 50/2005 Portugal | UN EN287/1 EN ISO 96062 | 5 years WARRANTY | professional use

Models	A	B	B2	C	C2	D	E	F	G	H	L	M	N	O	P
Length *(m)*	4.00	3.60	4.00	3.00	3.60	4.00	3.50	4.00	3.00	3.60	3.00	4.00	3.60	2.60	4.60
Overall width *(cm)*	37.00	37.00	37.00	37.00	37.00	41.00	41.00	50.00	41.00	50.00	50.00	52.00	52.00	37.00	37.00
Height *(cm)*	10.50	10.50	10.50	10.50	10.50	13.50	13.50	15.00	13.50	15.00	15.00	20.00	20.00	10.50	10.50
Weight per ramp *(KG)*	31.20	28.00	33.00	24.00	30.00	40.40	36.50	53.40	31.00	48.50	47.00	66.00	58.00	21.00	39.00
Capacity per pair *(KG)*	1 400	1 700	1 600	1 800	2 200	2 800	3 300	4 000	4 000	4 960	5 400	7 060	8 500	2 200	1 200
Reference	**10644**	**10645**	**10646**	**10647**	**10648**	**10649**	**10650**	**10651**	**10652**	**10653**	**10654**	**10655**	**10656**	**10657**	**10658**

Models	Q	R	S	T	U	ALsb*	BLsb*	CLsb*	DLsb*	ELsb*	TL	NL	ML	IL
Length *(m)*	2.50	4.50	4.50	3.00	4.60	1.80	2.20	2.60	3.00	3.60	3.00	3.60	4.00	4.60
Width *(cm)*	41.00	41.00	50.00	52.00	52.00	35.00	35.00	35.00	35.00	35.00	62.00	62.00	62.00	62.00
Height *(cm)*	13.50	13.50	15.00	20.00	20.00	7.50	7.50	7.50	7.50	7.50	20.00	20.00	20.00	20.00
Weight per ramp *(KG)*	25.00	43.00	58.50	50.00	74.00	13.00	15.00	17.70	20.00	23.00	53.00	63.00	72.00	79.00
Capacity per pair *(KG)*	5 000	2 400	3 000	9 320	6 000	1 600	1 600	1 000	800	600	8 500	8 000	7 000	6 000
Reference	**10659**	**10660**	**10661**	**10662**	**10663**	**10664**	**10665**	**10666**	**10667**	**10668**	**10669**	**10670**	**10671**	**10672**

***sb* ramps have no raised edges.**