TELEFLY LIGHT

Telefly with a narrower platform

Telescopic individual work platform for professional use, made of aluminium. With steps 2.7cm deep spaced 28cm apart and a 57x44cm platform. Offers 7 different working heights and can be used on uneven surfaces such as ramps and stairs. Access width of 55cm. Ideal for professional work.

TECHNICAL SPECIFICATIONS

- Number of steps: 4+3 and 6+4;
- Step spacing: 28cm;
- Steps: 2.7x2.7cm;
- Platform 57x44cm;
- Guardrail height: 1.00m;
- Toeboard height: 10cm;
- Inner profile: 57x27mm;
- External profile: 64x30mm;
- 2 wheels: Ø150mm;
- Wide base (maximum stability);
- Ergonomic PVC end cap;
- Telescopic lifting hooks;
- User and maintenance manual;
- Identification label.

PROTECTION & SAFETY 360°




OPTIONS

- Access handrails (4-step/6-step)





Opening/closing the guardrails



Telefly Light 4-3 steps

Decree-Law 50/2005 Portugal | Certified EN 131 Standard | 5 years WARRANTY | professional use | 150 KG

No. of steps	4+3	6+4
Platform height *(m)*	1.00	1.52
Overall height *(m)*	1.52	2.32
Working height *(m)*	3.50	4.30
Base dimensions *(m)*	0.80 x 1.60	0.80 x 2.17
Closed width *(m)*	0.31	0.31
Weight *(kg)*	20.50	30.50
Reference	**10862**	**10865**