TEMPO CONFORT

A professional aluminium scaffold designed for quick assembly and continuous worker protection with 360º handrails. Access is from within the scaffold using comfortable 45º stairways, with intermediate platforms between levels for safe ascent and descent. Ideal for maintenance and repair work.



Tempo Confort

TECHNICAL SPECIFICATIONS

- Width: 1.35m;
- 3 lengths available: 2.00 - 2.50 - 3.00m;
- 45º stairways with handrails;
- Step depth: 10cm;
- Maximum working height: 9.79m;
- Capacity for 2 people;
- Step spacing: 30cm;

EQUIPMENT

- 4 nylon wheels with double pedal brake (Ø 150mm);
- Frame heights: 1.20 - 1.50 - 1.80 - 2.10m;
- User and maintenance manual and certificate of conformity with EN1004

This scaffold follows the assembly method of **European Standard EN1004 1.2**:

- Distance from ground to platform < 3.40m
- Distance between successive platforms < 2.25m
- Platforms added to module P to facilitate assembly and dismantling









MAX. HEIGHT *(m)*			PLATFORM		COMPONENTS		REFERENCES		
Plat.	**Total.**	**Work.**	**With trapdoor**	**No trapdoor**	**Toeboards**	**Stabilisers**	**2.00m**	**2.50m**	**3.00m**
2.39	3.90	4.39	1	1	1	4P	390200	390250	390300
2.69	4.20	4.69	1	2	1	4P	420200	420250	420300
2.99	4.50	4.99	1	2	1	4P	450200	450250	450300
3.29	4.80	5.29	1	2	1	4P	480200	480250	480300
3.59	5.10	5.59	1	2	1	4M	510200	510250	510300
3.89	5.40	5.89	1	2	1	4M	540200	540250	540300
4.19	5.70	6.19	1	1	1	4M	570200	570250	570300
4.49	6.00	6.49	1	2	1	4M	600200	600250	600300
4.79	6.30	6.79	1	3	1	4M	630200	630250	630300
5.09	6.60	7.09	1	3	1	4M	660200	660250	660300
5.39	6.90	7.39	1	3	1	4M	690200	690250	690300
5.69	7.20	7.69	1	3	1	4G	720200	720250	720300
5.99	7.50	7.99	1	3	1	4G	750200	750250	750300
6.29	7.80	8.29	1	2	1	4G	780200	780250	780300
6.59	8.10	8.59	1	3	1	4G	810200	810250	810300
6.89	8.40	8.89	1	4	1	4G	840200	840250	840300
7.19	8.70	9.19	1	4	1	4G	870200	870250	870300
7.49	9.00	9.49	1	4	1	4G	900200	900250	900300
7.79*	9.30*	9.79*	1	4	1	4G	930200	930250	930300

* Maximum height for outdoor use with stabilisers

ACCESSORIES AND OPTIONS

Internal ladder
Hatch platform
Stabiliser *(unit)*
Intermediate handrails
2 end handrails
Handrails for ladder base (2/3 steps)
Handrails for ladder base (4/7 steps)
Open entrance frame
Internal guardrail
2-step ladder base
3-step ladder base
4-step ladder base
6-step ladder base
7-step ladder base
Triple safe guardrail