## HORUS

STEP LADDERS

Professional use stool made of ribbed aluminum. The steps are welded to the amounts leading to a very solid and sturdy structure. Horus has a large bearing surface in the soil that prevents sliding or swing the ladder, even when the operator supports the feet on the edge of the platform. Wide aluminum platform injected, non-slip, very durable and comfortable.

## **TECHNICAL**

- Distance between steps: 25 cm;
- Steps nonskid plans: 8 cm;
- Capacity: 150 kg;
- · Closed width: 16 cm;
- Number of steps: 2 4;
- Height platform: from 0,42 to 0,84 m;
- Base width: from 53 to 60 cm.

## EQUIPMENT

- Non-slip aluminum tray (40x30 cm);
- · Bar anti-opening/ accidental closing;
- Non-slip rubber plates with ergonomic design;
- · Reinforcements anti-flexion in larger steps;
- Use and maintenance manual;
- · Certificate of conformity with EN 14183;
- Identification label.







REF		m m	<b>M</b>	m	<b>.</b> 	m	KG	€
10033	2	0.69	0.42	2.42	0.53	0.16	3.70	
10034	З	0.90	0.62	2.62	0.56	0.16	4.50	
10035	4	1.13	0.84	2.84	0.60	0.16	5.30	





Law





