LOFT

Telescopic loft ladder with automatic closure.

Made of very sturdy anodized aluminum, especially designed for domestic use. It is designed for quick and easy assembly. It is quite light and features a wide ramping 9 cm steps that allow the rise and fall with comfort and safety. To open the ladder simply release the safety hook and within seconds the staircase will open up. To close the ladder must press the two securing tabs positioned in the first step and then push up the stairs without any effort thanks to a spring system. Available in two sizes with 9 to 10 steps.

Loft has minimum opening dimensions thanks to the telescopic system. The ladder requires only about 1,40 m from the open wall. The housing is made of galvanized steel timber with lid, as equipped with a lock and open bar.


Note: The ladder can be mounted and used without the drawer, both are sold and delivered separately.


TECHNICAL

- Number of steps: 9 to 10 steps;
- Adjustable maximum height: from 2,45 to 3,00 m;
- Base width: 45 cm;
- Width at top: 43 cm;
- Rising width: 30 cm;
- · Distance between steps: 28 cm;
- · Capacity: 150 kg;
- Weight: 13 to 18 kg.

EQUIPMENT

- Non-slip PVC plates;
- Quick locking system;
- Labels and use instructions.









LOFT - ALUMINUM TELESCOPIC LADDER				
REF	Dimensions Closed	Height Ceiling	KG	€
	т	т		
10766	0.52x0.60	2.35 - 2.45	13.00	
10767	0.52x0.90	2.52 - 2.65	18.00	
10768	0.52x1.10	2.65 - 3.01	18.00	
	STO	EL BOX WOOD T		
STEEL BUX WOOD TOP				
10769	0.60X1.00			
10770	0.60X1.20			



84