

OPTIMUS

Ladder made of aluminum.

Accesses comfortably at different heights with a stable attachment to the soil and place of support. The ladder is provided with railings on both sides to protect the user both in ascent and in descent. Large tilting supporting legs, made of PVC, used to change the ladder tilt adapting to the ground and maintaining stability. By modifying the support height, the slope varies the steps while maintaining a horizontal position for convenient ascent. The parts support platform and shoes have holes to fix power and thus avoid accidental slips, depending on the terrain. It is perfect for roofs or very sloping ceilings.

TECHNICAL

- Non-slip plates for a perfect support to the ground;
- Capacity: 150 kg;
- Shoes that enable fixation to the ground;
- Screws included;
- Non-slip grooved aluminum in steps depth: 255 mm;
- Width: 600 mm;
- Integrated anti-pumping safety device.



Inclination 71°



Inclination 19°



Decree
50/2005
Law

Certificate
EN 131
Standards

5 years
WARRANTY

professional use

150
KG

REF	inclination 15°	inclination 60°		mm	KG	€
		min.	max.			
	mm	mm				
180100	5	477	1320	2690 x 690 x 750	33.00	
180101	6	575	1600	2990 x 690 x 750	40.00	
180102	7	673	1884	3290 x 690 x 750	44.00	
180103	8	770	2167	3590 x 690 x 750	52.00	
180104	9	868	2451	3890 x 690 x 750	59.00	
180105	10	966	2735	4190 x 690 x 750	65.00	
180106	11	1063	3018	4490 x 690 x 750	72.00	
180107	12	1161	3302	4790 x 690 x 750	78.00	

REF	inclination 15°	inclination 60°		mm	KG	€
		min.	max.			
	mm	mm				
180108	13	1259	3586	5090 x 690 x 750	85.00	
180109	14	1356	3869	5390 x 690 x 750	91.00	
180110	15	1454	4153	5690 x 690 x 750	98.00	
180111	16	1552	4437	5990 x 690 x 750	104.00	
180112	17	1649	4702	6290 x 690 x 750	110.00	
180113	18	1747	5004	6590 x 690 x 750	117.00	
180114	19	1845	5288	6890 x 690 x 750	123.00	
180115	20	1942	5571	7190 x 690 x 750	130.00	