

PALCO COMPACT

Palco Compact 400x500 mm.

Built in extruded aluminum with a strong and durable quality, increase gradient is large and convenient, has an inclination of 48 ° with skid-resistant steps 200 mm depth and a 210 mm distance between steps. To avoid excessive transportation costs ladder is commercialized disassembled, following a book assembly instructions. The back is almost perpendicular to the ground to allow the user access to a close wall or machines.

TECHNICAL

- Number of steps: 2-5;
- Distance between steps: 21 cm;
- Depth steps: 20 cm;
- Profile amount: 65x25 mm;
- Width rise: 60 cm;
- Climb the slope grade: 48°;
- Dimensions platform: 40x50 cm;
- Rail height: 100 cm;
- Platform height: from 0,42 to 1,05 m;
- Overall height of the ladder: from 1,33 to 1,96 m;
- Capacity: 150 kg.





EQUIPMENT

- Handrails;
- 2 wheels;
- 2 wheels of 125 mm in diameter;
- Use and maintenance manual;
- Identification label.

OPTIONS

- 2nd side railing rise;
- Ladder without wheels;
- Tool holder tray;
- Closing door.



REF					KG	€
	m	m	m	m		
10307	2	0.42	1.33	2.42	16.00	
10308	3	0.63	1.54	2.63	20.00	
10309	4	0.84	1.75	2.84	25.00	
10310	5	1.05	1.96	3.05	30.00	

