PRIME DUPLA

Ladder designed for the toughest jobs.

TECHNICAL

- · Sliding wheels;
- · Adjustable base stabilizer;
- · Nylon reinforcement inside stabilizer seat;
- · Assembly and use;
- · Cast aluminum opening system;
- Bar that prevents uncontrolled closure or opening of the stairs;
- · Non-slip rubber feet;
- Extension locking device to prevent movement of the stairs when the safety limit is reached;
- · Safety device when used as a stepladder;
- · Steps plans in use;
- · Capacity: 150 kg;
- · Step distance: 28 cm;
- · Distance between steps: 30x30 mm.

EQUIPMENT

- · Patented adjustable base;
- Base provided standard on double and triple Prime model;
- Constructed of aluminum, this system allows you to adjust the stairs on uneven ground, giving it always vertically;
- 2 steel pins allow the user to make the adjustment of the base, it can still be removed whenever it is necessary to use the staircase extensible model in tight spaces, etc;
- · Setting up to 16 cm Regulation of 2-2 cm.













REF		m	m	↑	mm	KG	€
10755	6+7	3.45	2.25	2.10	67x27	12.00	
10756	8+9	4.65	2.85	2.70	67x27	14.00	
10757	10+11	5.85	3.45	3.30	67x27	17.00	
10758	12+13	6.75	4.05	3.80	67x27	19.00	
10759	13+14	7.65	4.35	4.10	84x27	23.00	













