


OPTIMUS



Professional-use ladder manufactured in aluminium. Allows access to different heights by being fixed and supported directly on the floor. With 25 cm deep steps, the inclination varies while the steps always remain parallel to the floor. The support parts, platform and non-slip feet adapt to the surface, preventing slipping. Ideal for access to very steep roofs or ceilings.

TECHNICAL INFO

- Number of steps: 5 to 20;
- Step depth: 25 cm;
- Total height: 0.48 to 5.57 m;
- Climbing angle: 19°–45°–71°;
- Handrails: 1.00 m;
- Width: 60 cm;
- Profile: 60 × 30 × 2 mm;
- Handrails on both sides;
- Pivoting PVC support feet;
- Fixing hardware included;
- Anti-closing safety device;
- User and maintenance manual;
- Certificate of conformity with the EN131 standard;
- Identification label.



Optimus 9 steps

Decreto
50/2005
Lei

Certificado
EN 131
Norma

5 anos
GARANTIA

Number of steps	5	6	7	8	9	10	11	12
Inclined height 19°-71° (m)	0.48 - 1.32	0.58 - 1.60	0.68 - 1.88	0.77 - 2.17	0.87 - 2.45	0.97 - 2.74	1.06 - 3.02	1.16 - 3.30
Weight (kg)	33.00	40.00	44.00	52.00	59.00	65.00	72.00	78.00
Reference	10819	10820	10821	10822	10823	10824	10825	10826
PRICE (€)	2 778.30	3 241.35	3 762.28	4 341.09	4 746.26	5 267.19	5 788.13	6 251.18

Number of steps	13	14	15	16	17	18	19	20
Inclined height 19°-71° (m)	1.26 - 3.59	1.36 - 3.87	1.45 - 4.15	1.55 - 4.44	1.65 - 4.70	1.75 - 5.00	1.85 - 5.29	1.94 - 5.57
Weight (kg)	85.00	91.00	98.00	104.00	111.00	117.00	124.00	130.00
Reference	10827	10828	10829	10830	10830.2	10830.3	10830.4	10830.5
PRICE (€)	6 772.11	7 350.92	7 756.09	8 242.29	8 797.95	9 261.00	9 724.05	10 244.98

When calculating the working height, add 2 m for the user with their arms fully extended.