

J400 - FIXED PLATFORM

Fixed platform ladder, developed for safe access to negative levels. The J400 was designed to ensure greater stability, safety and comfort when working in excavations, foundations, maintenance and technical access on site. The aluminium structure makes the equipment strong and easy to handle, while the platform provides a wider and safer support area. Available from 6 to 14 steps, it adapts to different working heights and site requirements.

TECHNICAL CHARACTERISTICS

- Number of steps: from 6 to 14;
- Distance between steps: 25.7cm;
- Step depth: 10cm;
- Profile: 65x25mm;
- Platform: 55x40cm;
- Total width: 80cm;
- Exit width: 55cm;
- Aluminium platform;
- Access handrails;
- Use and maintenance manual;
- Identification label.



J400 - 8 steps

Number of steps	6	7	8	9	10	11	12	13	14
Platform height (m)	1.49	1.75	2.00	2.26	2.51	2.77	3.03	3.29	3.54
Maximum total height (m)	2.60	2.86	3.11	3.37	3.63	3.88	4.14	4.40	4.65
Profile (mm)	65x25	65x25	65x25	65x25	65x25	65x25	65x25	65x25	65x25
Weight (kg)	17.00	17.50	18.00	20.50	21.50	22.50	23.50	24.50	27.00
Reference	14106	14107	14108	14109	14110	14111	14112	14113	14114

When calculating the working height, consider 2m for the user with arms fully extended.